



US006644638B1

(12) **United States Patent**
McCormick

(10) **Patent No.:** **US 6,644,638 B1**
(45) **Date of Patent:** **Nov. 11, 2003**

(54) **ELECTRIC CLAMP**

(75) Inventor: **Peter E. McCormick**, Dallas, TX (US)

(73) Assignee: **Delaware Capital Formation, Inc.**,
Wilmington, DE (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/321,880**

(22) Filed: **Dec. 17, 2002**

Related U.S. Application Data

(63) Continuation-in-part of application No. 09/887,293, filed on
Jun. 22, 2001.

(51) Int. Cl.⁷ **B25B 1/06**

(52) U.S. Cl. **269/225**; 269/32; 269/228

(58) Field of Search 269/32, 225, 201,
269/228, 3, 6, 237-239, 243

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,599,957 A *	8/1971	Blatt	269/32
4,458,889 A	7/1984	McPherson et al.	
4,637,597 A	1/1987	McPherson et al.	
4,723,767 A	2/1988	McPherson et al.	
4,770,401 A *	9/1988	Donaldson	269/249
4,793,602 A	12/1988	McPherson et al.	

4,854,564 A 8/1989 McPherson et al.

4,904,909 A 2/1990 Zeeland et al.

5,165,670 A 11/1992 Sawdon

5,912,541 A 6/1999 Bigler et al.

5,996,984 A 12/1999 Takahashi

6,220,588 B1 * 4/2001 Tunkers 269/32

6,354,580 B1 * 3/2002 Nagai et al. 269/225

* cited by examiner


Primary Examiner—Lee D. Wilson

(74) *Attorney, Agent, or Firm*—Brian F. Russell; Bracewell
& Patterson, L.L.P.

(57) **ABSTRACT**

An electrically powered clamp has a housing, a motor attached to the housing, a ball screw driven by the motor via a belt, and a linkage driven at one end by the ball screw such that the linkage rotates an output shaft attached to the other end of the linkage. The motor and belt drive the ball screw between a fully extended position to rotate the shaft to a clamped position, and a fully retracted position to rotate the shaft to an unclamped position. A built-in computer monitors and controls the clamp. The clamp can also be controlled and monitored by a remote pendant. Indicator lights on the housing and remote pendant convey clamp status information. The clamp is programmable and can memorize the clamped and unclamped positions. The clamp uses velocity and position feedback to determine appropriate drive mode. Torque monitors and timers determine if the clamp becomes stuck.

22 Claims, 7 Drawing Sheets







Fig. 3





Fig. 6







Fig. 7




Fig. 8









Fig. 9





1

ELECTRIC CLAMP

The present application is a continuation-in-part of U.S. patent application Ser. No. 09/887,293, filed Jun. 22, 2001, and entitled, Electric Clamp, and is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

1. Technical Field

This invention pertains to power clamps and more particularly to clamps driven by electric motors. Clamps are used to secure an object to aid assembly or to secure it during transport from one location to another.

2. Description of the Related Art

The robotics and automation industry heavily relies on power clamps for securing objects such as mechanical or electrical components so those components can be integrated into an assembly or moved from one assembly station to another. Clamps of various sizes, shapes, and configurations have been used to secure objects ranging in size from as small as electronic circuit boards to as large as entire automobile body panels. Clamps can be comprised of opposing members, but are more commonly mounted to a work surface and use one arm to pin the object against the work surface.

The majority of clamps currently used in the automation industry are pneumatically powered. This is primarily due to the significantly greater power obtainable from a pneumatically powered clamp compared to existing electrical clamps of similar size. Disadvantages of prior versions of electric clamps include being large, complex, delicate, or expensive.

SUMMARY OF THE INVENTION

The present invention uses an innovative design to produce an electric clamp with high clamping power in a small and relatively inexpensive package. In one embodiment, the clamp of the present invention comprises an electrically powered clamp having a housing, a motor attached to the housing, a ball screw driven by the motor via a belt, and a linkage driven at one end by the ball screw such that the linkage rotates an output shaft attached to the other end of the linkage. The motor and belt drive the ball screw between a fully extended position to rotate the output shaft to a clamped position, and a fully retracted position to rotate the output shaft to an unclamped position. A built-in controller monitors and controls the clamp. The clamp can also be controlled and monitored by a remote pendant. Indicator lights on the housing and remote pendant convey clamp status information. The clamp is programmable and can memorize the clamped and unclamped positions. The clamp uses velocity and position feedback to determine appropriate drive mode. Torque monitors and timers determine if the clamp becomes stuck.

BRIEF DESCRIPTION OF THE DRAWINGS

So that the manner in which the described features, advantages and objects of the invention, as well as others which will become apparent, are attained and can be understood in detail, more particular description of the invention briefly summarized above may be had by reference to the embodiments thereof that are illustrated in the drawings, which drawings form a part of this specification. It is to be noted, however, that the appended drawings illustrate only typical preferred embodiments of the invention and are therefore not to be considered limiting of its scope as the invention may admit to other equally effective embodiments.

2

FIG. 1 is a side view of an electric clamp constructed in accordance with one embodiment of the present invention showing the clamp in its clamped position.

FIG. 2 is a side view of the clamp of FIG. 1, but showing the clamp in its unclamped position.

FIG. 3 is a section view along Section 3—3 of FIG. 2.

FIG. 4 is a top view of the clamp of FIG. 1 with cover removed.

FIG. 5 is a top view of the clamp of FIG. 1 with cover on and remote pendant attached.

FIG. 6 is an end view of the clamp of FIG. 1.

FIG. 7 is a schematic diagram of the electronics used in the clamp of FIG. 1.

FIG. 8 is a side view of an electric clamp constructed in accordance with a second embodiment of the present invention showing the clamp in its clamped position.

FIG. 9 is a partial isometric view of a drive system of the electric clamp of FIG. 8.

FIG. 10 is a side view of an electric clamp constructed in accordance with a third embodiment of the present invention showing the clamp in its clamped position.

FIG. 11 is a side view of the clamp of FIG. 10, but showing the clamp in its unclamped position.

FIG. 12 is a side view of an electric clamp constructed in accordance with a fourth embodiment of the present invention showing the clamp in its clamped position.

FIG. 13 is a side view of the clamp of FIG. 12, but showing the clamp in its unclamped position.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

FIGS. 1 and 2 illustrate an electric clamp 10. Electric clamp 10 has a housing 12 that serves as a base on and inside of which other structural elements are mounted. Housing 12 protects the housed components. Housing 12 can be made of any durable, lightweight material, but is preferably metal or another conductive material that can be electrically grounded. It is desirable that housing 12 be easily formed into complex shapes to allow for space-efficient integration of various components.

Electric clamp 10 further comprises a motor 14. Motor 14 is a conventional electrically driven motor that mounts to housing 12 and serves to drive motor gear 16. The motor 14 can be virtually any type of electric motor. Different applications may dictate whether the motor is preferably an ac or dc motor, a stepper motor, an induction motor, a brushless motor, or other less common motor type. A dc motor offers the advantages of low cost and simple control requirements, but other requirements may dictate other motor types. Larger motors are generally required for larger clamps.

Motor gear 16 is on the output shaft 17 of motor 14 and engages ball nut gear 18 (FIG. 3). Ball nut gear 18 attaches to and drives ball nut hub 20 in response to motor gear 16. Hub 20 attaches to and drives ball nut 22. As ball nut 22 is rotated in place by hub 20, ball screw 24, a threaded shaft going through ball nut 22, advances or retreats depending on the direction of rotation of ball nut 22. The gear ratios for motor gear 16 and ball nut gear 18 can be chosen to produce a desired torque or rotational rate for ball nut 22. That determines the power or rate of advance/retreat of ball screw 24.

One end of ball screw 24 pivotally attaches to one end of link 26. The opposite end of link 26 pivotally attaches to an end of link 28. Clamp output shaft 30 is rigidly attached to

3

the opposite end of link 28. Clamp arm 31 (shown in phantom line) is mounted to clamp output shaft 30. Clamp arms of various sizes can be attached, depending on a user's needs.

In the embodiment of FIG. 1, slave motor 32 is used to provide additional torque. Slave motor 32 is wired in parallel with motor 14 to assist motor 14. The same voltage is applied to both motors. Slave motor 32, through its output shaft 33, drives motor gear 34, which drives ball nut gear 18, each identical in operation to motor 14, output shaft 17, and motor gear 16, respectively.

In the basic operation of clamp 10 of FIG. 1, power is supplied to motors 14 and 32 to drive motor gears 16 and 34. Those gears drive ball nut gear 18, which drives hub 20. Hub 20 rotates ball nut 22. Ball nut 22 drives ball screw 24, which drives links 26 and 28, rotating clamp output shaft 30 to a fully clamped (FIG. 1) or fully released (FIG. 2) position, depending on the direction of rotation of ball nut 22.

FIG. 2 shows an optional brake 37 attached to the motor shaft 33 of slave motor 32 that can be used to stop slave motor 32, and therefore stop the motion of clamp 10. Brake 37 may be required if large clamp arms having high rotational inertia or significant weight are used. In those situations, the inertia or moment may cause clamp 10 to move toward the clamped or unclamped position even though no power is applied. Brake 37 prevents such drift.

While the structural elements described above are sufficient to describe the basic configuration and operation of clamp 10, there are many other elements that enhance its functionality. Encoder 38 mounts to motor 14. The encoder 38 shown in FIG. 1 attaches to motor shaft 17 of motor 14. Encoder 38 provides motor angle information for position feedback. The motor angle information tells how far motor 14 has rotated from the clamped or unclamped position, therefore determining the position of clamp arm 31. An absolute or incremental encoder can be used, or another type of motor position sensor, such as a resolver, can be used.

Ball nut 22 is supported by thrust bearing 40. Thrust bearing 40 mounts between housing 12 and ball nut 22 and carries the thrust load generated during the clamping process. Similarly, ball screw 24 is supported by support bearing 42. Bearing 42 mounts between housing 12 and ball screw 24 and prevents lateral loads from being transferred to ball screw 24 during extreme loading conditions. Bearing 42, in conjunction with retainer ring 44, also acts as a barrier to prevent grease from moving from links 26, 28 into the vicinity of ball nut 22.

Stop collar 46 is adjustably fixed to ball screw 24 and physically inhibits further retraction of ball screw 24 once stop collar 46 is pulled into contact with bearing 42. This feature is useful to prevent clamp 10 from opening too far. The need for restriction commonly arises when objects in the vicinity of clamp 10 interfere with the full range of motion of clamp 10, particularly when longer clamp arms are used.

FIG. 4 shows thumb wheel 48 attached to the motor shaft of slave motor 32. Wheel 48 allows clamp 10 to be moved without electrical power. This is useful when no power is available, such as during initial setup, or when the drive control electronics (described below) are unavailable. This can occur when clamp 10 becomes extremely stuck or the electronics themselves fail. Wheel 48 is normal concealed and protected by access cover 50, as shown in FIG. 5.

FIG. 5 also shows clamp buttons 52 and 54. Buttons 52, 54 allow a user to drive clamp 10 to a clamped or unclamped position, respectively. The motion produced is relatively

4

slow in both directions and clamp 10 moves only while a button is depressed. Buttons 52, 54 are located in recesses 56 (FIG. 1) in cover plate 58. Recesses 56 are covered to prevent infiltration of contaminants and to prevent inadvertent engagement of buttons 52, 54. A pointed tool, such as a screwdriver, is needed to actuate buttons 52, 54.

Also located on cover plate 58 are status lights 62, 64. Clamped status light 62, when lit, indicates clamp 10 is very close to the programmed clamped position. (The programmable aspects are discussed below.) Similarly, unclamped status light 64 lights up when clamp 10 is very close to the programmed unclamped position. In addition, there are indicator lights 66 (FIG. 6) on control circuit board 68 (FIG. 2) within housing 12. Indicator lights 66 are viewed through window 70 (FIG. 1) and provide an operator information about the operational state of clamp 10.

Electrical power is primarily supplied to clamp 10 through control cable 72 (FIG. 6), which fastens to cover plate 58 and electrically connects a wire bundle to electronics within housing 12. Power could be dc, ac, 24 volts, or 48 volts—a preferred embodiment uses 24 volts dc. Higher voltages, such as 110 or 220 ac voltages, could be used, but are generally considered unacceptable because of safety concerns. Electrical power is typically provided by an external power supply with enough current capacity to service several clamps.

Other electrical signals, such as a command signal from the user or clamp status information, are also transmitted through control cable 72. The electronics within housing 12 include control circuit board 68 (FIG. 1). Control board 68 has the circuitry necessary to control clamp 10.

FIG. 7 shows conceptually the electronic components comprising control board 68. Power conditioner 74 is used to provide clean 5 and 15 volts dc signal to control board 68. A CPU 76 mounted to control board 68 controls all aspects of the operation of clamp 10. CPU 76 comprises timers, counters, input and output portals, memory modules, and programmable instructions to regulate motion algorithms, error recovery, status messaging, test display, limit adjustment, and pushbutton control. Indicator lights 66 are connected to CPU 76.

Clamp 10 has pushbuttons 79, 81, 83, 85 on the exterior of housing 12 to permit a user to adjust the position to which CPU 76 will command the motor to move upon receiving a clamp or unclamp command. There is also a pushbutton 78 allowing CPU 76 to learn and memorize the clamped position based on when the motor stalls. This is usually a quicker way to set the programmed clamp position than by using pushbuttons 79, 81, 83, 85. All of those pushbuttons 78, 79, 81, 83, 85, as well as clamp/unclamp buttons 52, 54, are illustrated in FIG. 7.

CPU 76 controls motor drive circuit 80 and enabling circuit 82. Those circuits 80, 82 supply the drive current sent to slave motor 32 and motor 14. Because motor drive circuit 80 is easily damaged by logically inconsistent electrical input, enabling circuit 82 is used to independently assure logically consistent input. If excess current is detected by current monitor 84, such as may occur if clamp 10 is stalled or stuck, the output from motor drive circuit 80 is inhibited. A user may set an over-current threshold using over-current circuit 86.

All user interfaces described above are also found on remote pendant 88 (FIG. 5). Thus, remote pendant 88 allows a user to operate clamp 10 some short distance from clamp 10. This can be useful if clamp 10 is placed deeply within an automation tool, making the interfaces on housing 12 inac-

5

cessible. Lights **90** equivalent to indicator lights **66** are found on remote pendant **88**, so clamp status information can be observed. Remote pendant power supply **91** (FIG. **5**) provides electrical power to clamp **10** through remote pendant **88** via connector **93** on cover plate **58**. This is useful if conventional power is unavailable, as is often the case in the early stages of building an automation system. Pushbuttons **92**, **94**, **96**, **98**, **100**, **102**, and **104**, provide the same functionality as pushbuttons **78**, **54**, **52**, **85**, **83**, **81**, and **79**, respectively, using remote pendant **88**.

Clamps used in the automation industry are commonly used in conjunction with hundreds of other clamps, each clamp performing a specific function in a carefully choreographed manner. Often the multitude of clamps is controlled by a central controller issuing commands to the various clamps at the proper time. Clamp **10** accepts such external control commands through interface **106** (FIG. **7**). Clamp **10** is typically isolated from the external controller using optical isolators **108**, however simple lights or light emitting diodes (LEDs) may also be used. The lights or LEDs can convey essential status information such as clamped, unclamped, or a fault condition. This information can be passed to the central controller as well.

Referring now to FIG. **8**, an alternate embodiment of the present invention is depicted as clamp **210**. Like the preceding embodiment, the components of clamp **210** are located entirely within its housing **212**, other than the clamp arm **231** and the remote pendant (not shown). The primary difference between clamp **210** and clamp **10** of FIGS. **1** and **2** is the belt drive assembly **201** (FIG. **9**) utilized by clamp **210**. Thus, clamp **210** is very similar to clamp **10**, but in this embodiment of the present invention, the direct gear-to-gear drive assembly of clamp **10** illustrated in FIGS. **1**–**3** is replaced by the belt drive assembly **201**. The belt drive assembly **201** uses at least one drive sprocket (two are shown: **216**, **234**), a drive belt **207**, and a center sprocket **218**. The sprockets **216**, **234**, and **218** have external teeth that engage internal grooves on the drive belt **207**. The drive sprockets **216**, **234** engage and drive the belt **207** which, in turn, drives the center sprocket **218**. The sprockets **216**, **234** are mounted to drive shafts **217**, **233**, which extend from motors **214**, **232**, respectively. These components are similar or identical to the drive shafts **17**, **33** and motors **14**, **32**, described above for the previous embodiment.

To maintain adequate separation, sprockets **216**, **234** are sufficiently spaced apart in a radial direction (relative to their axes of rotation) so as to not make direct contact with the center sprocket **218** that is located between sprockets **216**, **234**. Center sprocket **218** is mounted to and drives a ball nut hub **220** having internal threads. As ball nut hub **220** is rotated by center sprocket **218**, a ball screw **224** advances or retreats depending on the direction of rotation of ball nut **222**. Ball screw **224** is a threaded shaft going through ball nut hub **220**, and is otherwise identical in function to ball screw **24** as described above. The tooth ratios for sprockets **216**, **234**, **218**, and belt **207** are selected to produce a desired torque or rotational rate for ball nut hub **220**, which determines the power or rate of advance/retreat of ball screw **224**. Other than the components employed and operated by belt drive assembly **201**, clamp **210** utilizes the same elements and operates in an identical manner as the previously described embodiment including, for example, a sensor or encoder **238** on motor **214**. The ball screw **224** is coupled to a linkage **226** to manipulate an output shaft **230** and a clamp arm **231**.

Referring now to FIGS. **10** and **11**, a third embodiment of the present invention is depicted as an electric clamp **310**.

6

Electric clamp **310** has a housing **312** and a number of other components including a lead screw **324**, which are all entirely enclosed within housing **312**. Clamp **310** is similar to the preceding embodiments in many respects, but differs primarily in the manner in which it manipulates the output shaft **330** and clamp arm **331**. In particular, clamp **310** uses a single electric motor **314**, which is preferably a linear actuator, to advance and retreat a lead screw **324** extending axially through the motor **314**. Consequently, no separate ball nut hub or ball nut are required.

The lead screw **324** is further coupled to the output shaft **330** through components such as a linkage **326** and a piston **333**. The piston **333** is mounted in a chamber **335** that is located within the housing **312**. In this disclosure, the terms piston and chamber are not necessarily used in the conventional sense to include a sealing relationship. Rather, these terms are used to denote the relative motion of the components, i.e., substantial restriction of radial motion of the piston by the chamber, while allowing the piston to move axially within the chamber. In the version shown, motor **314**, lead screw **324**, and piston **333** are coaxial. The piston **333** is coupled to the lead screw **324** and the output shaft **330**, such that axial movement of the lead screw **324** by the electric motor **314** moves the piston **333** axially within the chamber **335**, and moves the output shaft **330** and the clamp arm **331** through a range of motion. The other components described above and used in conjunction with the previous embodiments are likewise available for use with and employed by clamp **310**. In this version of the invention, the control circuit **368** of electric clamp **310** is located in an upper portion of the housing **312**.

Referring now to FIGS. **12** and **13**, a fourth embodiment of the present invention is depicted as an electric clamp **410**. Clamp **410** utilizes many of the components and features of the preceding embodiments, including a housing **412** and an electric motor **414** with a drive shaft **417** that is rotatable about an axis. In the depicted embodiment, motor **414** is mounted to an exterior of the housing **412**, and drive shaft **417** protrudes into the housing **412**. A helical coupling **415** is mounted to drive shaft **417** and is coupled to a ball nut hub (not shown). A ball screw **424** extends axially through the ball nut hub such that the ball screw **424** is axially advanced and retreated by rotation of the ball nut hub. The ball screw **424** is entirely enclosed within the housing **412**. The housing **412** also contains a chamber **435** that is coaxial with the drive shaft **417**. A piston **433** is located in the chamber **435**, and the piston **433** is coupled to the ball screw **424** such that movement of the ball screw **424** by the electric motor **414** moves the piston **433** axially within the chamber **435**.

An output shaft **430** is also mounted to the housing **412**. The output shaft **430** has a linkage **426** coupled to the piston **433** for movement therewith, and a mounting portion for a movable element (clamp arm **431**) to permit the movable element to at least partially extend from the housing **412**, and move the clamp arm **431** between clamped and unclamped positions. As described above for the previous embodiments, clamp **410** also has a control circuit **468** located within an upper portion of the housing **412** for controlling the motor **414**, and a sensor **438**, such as an encoder, that provides a signal to the control circuit indicative of a current position of the clamp arm **431**. The sensor **438** is coupled to the drive shaft **417** via a set of gears **444**, and the signal provided to the control circuit is indicative of a rotational position of the drive shaft **417**. The clamp **410** further comprises a remote pendant (not shown), which is identical to the one described above.

The present invention offers many advantages over the prior art. Housing the electronics controlling the clamp

internally is a significant advantage. Using two motors in tandem is a new and useful arrangement for making a more powerful electric clamp while staying within industry size standards. The remote control provided by the remote pendant is another novel advantage, as is the ability to drive the clamp with power supplied through the remote pendant when normal power is unavailable. The use of an encoder rather than limit switches allows for more intelligent, and more easily modified control. Being able to manually move the clamp using the thumb wheel allows for quick remedy for stuck or defective control condition. The ability to program a clamped and an unclamped position is new and useful, as is the ability to use software to command the clamp to stop when an unrecoverable stuck condition is sensed. The clamp allows for automatic learning of the programmed clamp and unclamped positions, and allows a user to fine tune those positions, if desired.

While the invention has been particularly shown and described with reference to a preferred and alternative embodiments, it will be understood by those skilled in the art that various changes in form and detail may be made therein without departing from the spirit and scope of the invention.

What is claimed is:

1. An electric clamp, comprising:

a housing;

at least one motor mounted to the housing and having a drive shaft and a drive sprocket coupled to the drive shaft for rotation therewith;

a center sprocket radially spaced apart from the drive sprocket;

a drive belt engaging and extending between the drive sprocket and the center sprocket;

a ball nut hub mounted to the center sprocket for rotation therewith;

a ball screw extending axially through the ball nut hub such that the ball screw is advanced and retreated by rotation of the ball nut hub, wherein the ball screw is entirely enclosed within the housing;

an output shaft and a linkage linking the ball screw to the output shaft, said output shaft having a mounting portion for a movable element that permits the movable element to at least partially extend from the housing; and

a control circuit located within the housing for controlling the at least one motor.

2. The electric clamp of claim 1, wherein the at least one motor comprises a pair of electric motors, each having a drive shaft and a drive sprocket, wherein the center sprocket is located between the drive sprockets.

3. The electric clamp of claim 1, further comprising a clamp arm attached to the output shaft and at least partially extending from the housing.

4. The electric clamp of claim 3, further comprising a sensor that provides a signal to the control circuit indicative of a current position of the clamp arm.

5. The electric clamp of claim 4, wherein the sensor comprises an encoder and wherein the signal provided to the control circuit is indicative of a rotational position of the drive shaft.

6. The electric clamp of claim 1, further comprising a thumb wheel rigidly attached to the drive shaft of the at least one motor, the thumb wheel being accessible from an exterior of the housing for manually rotating the drive shaft.

7. The electric clamp of claim 6, wherein the thumb wheel is inside the housing but accessible through a port in the housing, the port of the housing being covered by a movable door.

8. The electric clamp of claim 1, further comprising a remote pendant attached by a remote pendant control cable to the housing and electrically connected to the control circuit.

9. The electric clamp of claim 1, further comprising:

one or more electrical switches mounted on the housing that actuate the motor to drive the output shaft toward at least one of a clamped position and an unclamped position.

10. An electric clamp, comprising:

a housing;

an electric motor mounted to the housing;

a lead screw extending axially through the electric motor such that the lead screw is advanced and retreated by the electric motor and the electric motor and the lead screw are coaxial, wherein the lead screw is entirely enclosed within the housing;

an output shaft and a linkage coupling the lead screw to the output shaft, said output shaft having a mounting portion for a movable element that permits the movable element to at least partially extend from the housing; and

a control circuit located within the housing for controlling the electric motor.

11. The electric clamp of claim 10, further comprising a clamp arm attached to the output shaft and at least partially extending from the housing.

12. The electric clamp of claim 11, further comprising a sensor that provides a signal to the control circuit indicative of a current position of the clamp arm.

13. The electric clamp of claim 12, wherein the sensor comprises an encoder and wherein the signal provided to the control circuit is indicative of a rotational position of the electric motor.

14. The electric clamp of claim 10, wherein the linkage further comprises a piston mounted in a chamber within the housing, the piston being coupled to the lead screw and the output shaft, such that movement of the lead screw by the electric motor moves the piston axially within the chamber which moves the output shaft through a range of motion.

15. The electric clamp of claim 10, further comprising a remote pendant attached by a remote pendant control cable to the housing and electrically connected to the control circuit.

16. The electric clamp of claim 10, further comprising:

one or more electrical switches mounted on the housing that actuate the motor to drive the output shaft toward at least one of a clamped position and an unclamped position.

17. An electric clamp, comprising:

a housing;

an electric motor mounted to the housing and having a drive shaft with an axis;

a ball nut hub coupled to the drive shaft for rotation therewith;

a ball screw extending axially through the ball nut hub such that the ball screw is advanced and retreated by rotation of the ball nut hub, wherein the ball screw is entirely enclosed within the housing;

a chamber located in the housing and coaxial with the drive shaft;

a piston located in the chamber, the piston being coupled to the ball screw such that movement of the ball screw by the electric motor moves the piston axially within the chamber;

9

an output shaft having a linkage coupled to the piston for movement therewith, and a mounting portion for a movable element to permit the movable element to at least partially extend from the housing; and
a control circuit located within the housing for controlling the at least one motor.

18. The electric clamp of claim 17, further comprising a clamp arm attached to the output shaft and at least partially extending from the housing.

19. The electric clamp of claim 18, further comprising a sensor that provides a signal to the control circuit indicative of a current position of the clamp arm.

20. The electric clamp of claim 19, wherein the sensor comprises an encoder coupled to the drive shaft via a set of

10

gears, and wherein the signal provided to the control circuit is indicative of a rotational position of the drive shaft.

21. The electric clamp of claim 17, further comprising a remote pendant attached by a remote pendant control cable to the housing and electrically connected to the control circuit.

22. The electric clamp of claim 17, further comprising:
one or more electrical switches mounted on the housing that actuate the motor to drive the output shaft toward at least one of a clamped position and an unclamped position.

* * * * *